
GLASS TO GLASS & GLASS TO ALUMINUM SEALING





P.32
Neutral Silicone

100% Solvent-free

Excellent Weatherproof & UV Resistant

Water Resistant High Elasticity P.72

Neutral Silicone

Fast Cure
Low Modulus
Excellent Adhesion



www.proloc.com.tr

www.proloc.com.tr



A neutral cure, silicone sealant, exclusively created for weather sealing and glazing applications. It forms a highly resistant weatherproof seal on windows and building facades.



Neutral cure, high performance silicone sealant designed for gap filling and sealing in a wide range of uses in building and construction. It combines the advantages of outstanding adhesion to building materials with non-corrosive and odourless curing.



Properties

- Provides permanent elasticity
- Not affected by exposure to sunlight, rain, snow and lasts over many years
- Exceptional resistance to temperature extremes
- Very low odour and non-corrosive
- Excellent flexibility and adhesion to porous and non-porous
- Substrates for large scale construction and glazing applications
- · Fast curing, low modulus, high elasticity
- High viscosity non-slump formulation

Application Areas

- Weather sealing and joint sealing for walls, windows and doors
- Sealing and mounting the window and door frames
- Sealing applications of marble, stone and other porous substrates

Properties

- One component, moisture-cured
- Excellent primerless adhesion to numerous porous and non-porous substrates
- Non-corrosive. Does not react with or corrode common building materials
- Excellent weather ability in direct sunlight, rain, snow and ozone
- Resistant to temperature extremes (-60 °C to +180 °C)
- Fast curing
- Low modulus, high elasticity
- 100% Silicone, solvent-free
- Very low odour

Application Areas

- Sealing of connection joints in building industry (brick, wall, concrete, PVC, wood, glass etc.)
- Weather seal applications
- Mounting of windows and doors
- Glazing works
- Sealing applications in kitchens and bathrooms

www.proloc.com.tr